Cover Styl

DATA JAMMER

GLASS



RANGE & FINISH

FAMILY **Data Privacy**

SUB-FAMILY **Screen Privacy**

CHARACTERISTICS

Width (cm)	**122 cm**
Length (m)	**30.5 m**
Thickness (µm)	**132 µm**
Composition	**PET + PVA**
Composition Release liner	**PET**
Storage in recommended conditions	**1 years**
Storage Temperature	**5°C-30°C**
Visible Light Transmission	**44%**
Warranty	**5 years**

CERTIFICATIONS

FIRE RATING (EN13501-1)
M1 (NF P92-507)

REACH / ROHS
Compliant

Non-contractual visuals and data, Cover Styl reserves the right to change the composition of its films at any time. The rendition of the colours and finishes on the computer may vary according to the screen and not give a true representation of the true appearance. We therefore recommend you order a sample on line or contact us so that we can examine the finish that best adapts to your requirements. Due to the slight differences in colour in production runs, we advise you to purchase the amount you require in one go to avoid any difference in appearance in the execution of your Cover Styl project.

Certified B Corporation

Cover Styl

DATA JAMMER

GLASS

APPLICATION, INSTALLATION & MAINTAINANCE

APPLICATION COMPATIBILITY

Facing UV rays	**Caution**

INSTALLATION

Installation Type	**Interior**
Installation Method	**Wet**
Installation Temperature	**12°C-38°C**

INSTALLATION GUIDELINES

- Before installation, thoroughly clean and degrease the glazing, removing all dust, grease and residues.
- Apply the film using Slide On (600-FO2) or Film On (600-F0355), diluted at 6 mL/L of water, and remove the application solution and air with a suitable squeegee.
- Data Jammer requires a special installation. The orientation of the film may vary depending on the display technology, so a preliminary test on the intended glazing and screen configuration is essential.
- Please refer to the dedicated installation instructions before proceeding.

MAINTENANCE GUIDELINES

Use Slide On (600-FO2) or Film On (600-F0355), diluted at 6 mL/L of water, for installation and cleaning.
Do not clean the film during the first month following installation, and do not apply stickers, labels or adhesives to the film. Clean the surface gently using a soft, non-abrasive cloth or sponge

Non-contractual visuals and data, Cover Styl reserves the right to change the composition of its films at any time. The rendition of the colours and finishes on the computer may vary according to the screen and not give a true representation of the true appearance. We therefore recommend you order a sample on line or contact us so that we can examine the finish that best adapts to your requirements. Due to the slight differences in colour in production runs, we advise you to purchase the amount you require in one go to avoid any difference in appearance in the execution of your Cover Styl project.

Certified B Corporation