



RANGE & FINISH

FAMILY	Data Privacy	SUB-FAMILY	Screen Privacy
--------	--------------	------------	----------------

CHARACTERISTICS

Width (cm)	122 cm
Length (m)	30.5 m
Thickness (µm)	132 µm
Composition	PET + PVA
Composition Release liner	PET
Storage in recommended conditions	1 years
Storage Temperature	5°C-30°C
Warranty	5 years

CERTIFICATIONS

FIRE RATING (EN13501-1) M1 (NF P92-507)	REACH / ROHS Compliant
--	---------------------------

APPLICATION, INSTALLATION & MAINTAINANCE

APPLICATION COMPATIBILITY

Facing UV rays

Caution

INSTALLATION

Installation Type

Interior

Installation Method

Wet

Installation Temperature

12°C-38°C

INSTALLATION GUIDELINES

- Before installation, thoroughly clean and degrease the glazing, removing all dust, grease and residues.
- Apply the film using Slide On (600-FO2) or Film On (600-F0355), diluted at 6 mL/L of water, and remove the application solution and air with a suitable squeegee.
- Data Jammer requires a special installation. The orientation of the film may vary depending on the display technology, so a preliminary test on the intended glazing and screen configuration is essential.
- Please refer to the dedicated installation instructions before proceeding.

MAINTENANCE GUIDELINES

Use Slide On (600-FO2) or Film On (600-F0355), diluted at 6 mL/L of water, for installation and cleaning.

Do not clean the film during the first month following installation, and do not apply stickers, labels or adhesives to the film. Clean the surface gently using a soft, non-abrasive cloth or sponge