



RANGE & FINISH

FAMILY	Data Privacy	SUB-FAMILY	Switch
--------	--------------	------------	--------

CHARACTERISTICS

Width (cm)	100 cm
Length (m)	1 m
Thickness (µm)	540 µm
Composition	PET
Composition Release liner	PET
Storage in recommended conditions	3 years
Storage Temperature	5°C-30°C
Warranty	2 years

CERTIFICATIONS

FIRE RATING (EN13501-1) M1 (NF P92-507)	REACH / ROHS Compliant
--	---------------------------

APPLICATION, INSTALLATION & MAINTAINANCE

APPLICATION COMPATIBILITY

Facing UV rays

Caution

INSTALLATION

Installation Type

Interior

Installation Method

Dry

Installation Temperature

12°C-38°C

INSTALLATION GUIDELINES

- Always clean the glass thoroughly before installation, using Crystal Antistatic Spray (600-ATS) and wear antistatic gloves during installation or handling.
- Apply dry only - never use water or soapy solution.
- Handle carefully: keep the film flat, do not bend, and protect the edges.
- Keep the top protective liner in place until the end of the installation.
- Do not install under frames or in areas subject to mechanical stress.
- Leave a 2-2.5 mm gap if installing multiple panels side by side.
- Sealing is not mandatory but recommended if the film is exposed to humidity or at risk of water contact. Use only neutral (non-acidic) silicone sealant along the film edge.
- All electrical connections must be performed by a licensed electrician, following the wiring diagram and using the recommended transformer.
- For best durability, avoid continuous ON mode - use a timer to ensure a daily power cutoff.

Wait 30 days before cleaning and only use a microfiber cloth with non-abrasive products.

MAINTENANCE GUIDELINES

Wait 30 days after installation before cleaning the E-Film surface.

Use a soft, lint-free microfiber cloth and a mild cleaning product, such as a 50/50 diluted isopropyl alcohol solution or an ammonia-free glass cleaner.

Wipe gently in one direction to avoid streaks.

Clean power switches and controllers with a dry cloth only.